

HELI

Reliable special designed instrument

Neutral indicator

Preheating indicator

Left turning indicator

Oil lever gauge

Seat switch

Hour meter

Low fuel lever alarm indicator

Hand brake indicator

Engine fault indicator
(for electronic-controlled engine)



(Item with * are optional)

Engine oil pressure alarm indicator

*Oil-water separation alarm indicator

Right turning indicator

Water temperature meter

Meter lighting indicator

*Filter block alarm indicato

No charging alarm indicator

*High torque converter oil temperature alarm indicator

■ Reliable special meter display the whole truck's working condition, fault detect and other important information completely which make the operator master the whole truck condition directly and conveniently.

Standard configurationOptional

Horn	Standard fork	Driver's cab	Torque converter oil temperature meter
Control valve	Integrated electric box	Warning light	Tilting cylinder bush
Wholly hydraulic-powered steering	Hydraulic oil circuit filter	High air exhausting device	Customer made color
Half enclosed seat	Flow regulator	Double air cleaner	Optional attachments
Backrest	Wide view mast	Suspension seat	Steel protection net
Back view mirror	Air intaking device	Lengthening fork extension	Double-tyre and protection device
Front combined lamp	Durable tread tyre	Warm air blower	Rotating seat for 1pg
Transmission oil filter	Lifting and tilting operation lever	Solid tyre	Single/dual fuel system
Engine flame out device	Traction pin	Widen fork arm carrier	Low speed alarm
Cable type parking brake	Head lamp	Wind shield	
Driver's tool	Hydraulic oil dipstick	Cleansing muffler	
Rear combined lamp	Overhead guard	Fire extinguisher muffler	
Backward buzzer	Torque converter oil dipstick	Fire extinguisher	
Tilt oil circuit self lock valve	Combined instrument	Rear working light	
Tilt adjustable steering column	Electro-hydraulic direction changing	Air conditioner (certain type)	
Overhead guard rain cover		Travelling control system	

2-3.5 t
H3 series Internal Combustion Counterbalanced Forklift Truck



www.heliforklift.net

HELI

H3 SERIES 2-3.5 t

Improved performance, superior quality



↓ Vibration 20% reduced

↓ Noise 3dB reduced

- > Cushion connection and wholly suspension driver's cab absorb whole truck's vibration effectively.
- > Noise around ear is reduced through down the tilting cylinder under the floor board and using fully closed patch type driver's cab.
- > Lower damping device inside the lifting system reduces mast shock and vibration, avoiding crash noise caused by goods falling to the ground.

↑ Workspace 45% increased

- > Space around foot is effectively increased through up steering unit and using suspension type inching.
- > The operation space is enlarged by heightened overhead guard and using large arc shape of the overhead guard's front leg
- > Semi-suspension seat, steering wheel with small diameter, electro-hydraulic direction changing and automobile type double joystick combined switch effectively improve driving comfort.

↑ Operator's view 20% improved

- > Operator's front view is improved through the assembling of stand wide view mast and lowering the dashboard.
- > Operator's rear view improved through the CAE optimal designed counterweight.



↑ Working efficiency 20% improved

- > Small turning radius makes steering flexible and easy.
- > The truck has fast lifting speed, good gradeability and high efficiency.
- > High working efficiency guarantees the truck could meet the requirements for various kinds of complicated work condition perfectly wherever at port, dock and railway station.

↑ Loading capacity increased over 5%

↑ Stability 5% improved

↑ Reliability 40% improved

- > The hot air reflow isolating device, optimal thermal dissipation duct and aluminum plate-fin type radiator improve cooling ability and ensure engine work reliability.
- > Automobile type oil filling cap and optimal oil filling channel structure and process ensure whole truck's safety.
- > The constant displacement pump load sensing steering system increases the lifting speed and reduces the hydraulic oil temperature.
- > The optimal design of key parts like frame, mast, overhead guard and steering axle improve the whole truck's safety and reliability.
- > The repositioning of whole truck's gravity center improve loading capacity, stability and safety.

↑ Engine hood open angle increased to 80°

- > Enlarged internal space is convenient for engine and transmission box maintenance.
- > Increased hood open angle contributes to quick and convenient maintenance.



ANHUI HELI CO., LTD.
Add / No.668, FangXing Road, Hefei, China
Fax / +86-551-63639966

Tel / +86-551-63639068(America); 63639258(Europe);
63639358(Asia); 63662105(Africa & Middle East);
63639530(Key Accounts Division); 63639531(Wheel loader)


* Our products are subject to improvements and changes without notice.

Catalog No.190711 Forklift Print


H3 SERIES 2-3.5t



Manufacturer and technical parameters							
Character							
1.01	Manufacturer			HELI			
1.02	Model			CPC20 / CPCD20 / CPQ(Y)D20	CPC25 / CPCD25 / CPQ(Y)D25	CPC30 / CPCD30 / CPQ(Y)D30	CPC35 / CPCD35 / CPQ(Y)D35
1.03	Rated capacity		kg	2000	2500	3000	3500
1.04	Load center		mm	500			
1.05	Operation mode			Seat-type			
Size							
2.01	Max.lifting height	H	mm	3000	3000	3000	3000
2.02	Mast overall height(Fork to the ground and mast be vertical)	H1	mm	2000	2000	2065	2180
2.03	Max.fork lifting height(With backrest)	H2	mm	4030	4030	4245	4235
2.04	Free lift height	H3	mm	165	165	160	170
2.05	Overall height(Overhead guard)	H4	mm	2150	2150	2170	2170
2.06	Min.ground clearance(At the mast)	H5	mm	115	115	135	135
2.07	Distance from the surface of the seat to the overhead guard	H6	mm	1030	1030	1030	1030
2.08	Traction pin height	H9	mm	275	275	280	280
2.09	Backrest height(Calculated from the surface of the fork)	H13	mm	1000	1000	1227	1222
2.10	Overall length(With fork/Without fork)	(L/L')	mm	3500/2580	3708/2638	3818/2748	3836/2766
2.11	Wheel base	L1	mm	1650	1650	1700	1700
2.12	Front overhang	L2	mm	473	473	478	496
2.13	Rear overhang	L3	mm	457	515	570	570
2.14	Overall width	W1	mm	1150	1150	1225	1225
2.15	Tread (Front tread/Rear tread)	(W3/W2)	mm	970/970	970/970	1000/970	1000/970
2.16	Fork adjustable range(the external of the fork)(Max./Min.)	W5	mm	1030/244	1030/244	1060/250	1060/250
2.17	Min.turning radius(Exterior)	r	mm	2170	2240	2400	2420
2.18	Min.turning radius(Interior)	r'	mm	180	180	200	200
2.19	Min.right angle stacking aisle width	Ra	mm	2200	2280	2380	2400
2.20	Mast tilting angle	α / β	%	6°/12°	6°/12°	6°/12°	6°/12°
2.21	Fork size	L4×W×T	mm	920×122×40	1070×122×40	1070×125×45	1070×125×50
Weight							
3.01	Total weight		kg	3420	3800	4370	4800
3.02	Weight distribution loaded (Front/Rear)		kg	4770/650	5480/820	6460/910	7470/830
3.03	Weight distribution unloaded (Front/Rear)		kg	1600/1820	1560/2240	1710/2660	1880/2920
Wheel and tyre							
4.01	Wheel number x = drive wheel (Front/Rear)			2X/2			
4.02	Tyre type(Front/Rear)			Pneumatic tyre			
4.03	Tyre size(Front/Rear)			7.00-12-12PR/ 6.00-9-10PR	7.00-12-12PR/ 6.00-9-10PR	28×9-15-12PR/ 6.50-10-10PR	28×9-15-14PR/ 6.50-10-10PR
4.04	Service brake			Hydraulic-Foot Pedal			
4.05	Parking brake			Mechanical-Hand Lever			



Ast: right angle stacking aisle width
a: Clearance
L4: Fork Length




CPQ(Y)D20
CPQ(Y)D20
CPC20
CPCD20

CPQ(Y)D25
CPQ(Y)D25
CPC25
CPCD25

CPQ(Y)D30
CPQ(Y)D30
CPC30
CPCD30

CPQ(Y)D35
CPQ(Y)D35
CPC35
CPCD35

Note: The vertical axis stands for load capacity and the horizontal axis stands for load center which is calculated from the front of the fork. The base point of the standard load refers to the center position of the cube with 1000mm length of side. When mast is tilted forward, nonstandard fork usage or load with over wide goods, load capacity will be reduced. Different load capacity in different load center can be known in time through load chart.



WIDE VIEW MAST													
Mast model	Max. lifting height mm	Load capacity (load center 500mm)					Mast overall height (fork to the ground)			Service weight			
		CPQ(Y)D20/ CPC20/CPCD20	CPQ(Y)D25/ CPC25/CPCD25	CPQ(Y)D30/ CPC30/CPCD30	CPQ(Y)D35/ CPC35/CPCD35		2-2.5t	3t	3.5t	CPQ(Y)D20/ CPC20/CPCD20	CPQ(Y)D25/ CPC25/CPCD25	CPQ(Y)D30/ CPC30/CPCD30	CPQ(Y)D35/ CPC35/CPCD35
M200	2000	2000	2500	3000	3500		1495	1570	1680	3340	3720	4280	4700
M250	2500	2000	2500	3000	3500		1745	1820	1930	3385	3765	4335	4750
M300	3000	2000	2500	3000	3500		1995	2080	2180	3420	3800	4370	4800
M330	3300	2000	2500	3000	3500		2145	2220	2330	3460	3840	4395	4830
M350	3500	2000	2500	3000	3500		2245	2320	2430	3480	3860	4420	4850
M370	3700	2000	2500	3000	3500		2345	2420	2530	3500	3880	4430	4870
M400	4000	2000	2500	3000	3500		2545	2620	2730	3565	3945	4490	4940
M425	4250	1900	2250	2850	3300		2670	2745	2855	3590	3970	4510	4970
M450	4500	1900	2250	2850	3300		2795	2870	2980	3615	3995	4535	4990
M500	5000	1700	2100	2700	3200		3045	3120	3230	3655	4035	4575	5040
M550	5500	*1600	*1950	*2400	*2500		3345	3420	3530	3740	4120	4745	5245
M600	6000	*1500	*1800	*2200	*2300		3595	3670	3780	3785	4165	4795	5285

Note: (1) *stands for the rated capacity when the front tyre is double-tyre. (2) When the front tyre of the 2-3.5t truck is double tyre, the service weight of the truck is the weight in the table plus 110kg.

Performance																	
Model		CPC20	CPCD20	CPC25	CPCD25	CPC30	CPCD30	CPC35	CPCD35	CP(Q)(Y)D20	CP(Q)(Y)D20	CP(Q)(Y)D25	CP(Q)(Y)D25	CP(Q)(Y)D30	CP(Q)(Y)D30	CP(Q)(Y)D35	CP(Q)(Y)D35
Max.drawbar pull (Loaded/Unloaded)	kN	14.5/12.3	16/12.8	18/12.4	18.7/13.8	17/14.5	19/14.5	18/14.5	21/14.5	15/12.5	16/12.8	15/12.3	16.5/12.4	17/13.5	18/13.5	18/13.5	20/13.5
Max.Gradeability (Loaded/Unloaded)	%	30/25	39/28	27/23	35/23	21/23	29/22	15/22	23/22	30/25	39/28	27/23	35/23	21/23	29/22	15/22	23/22
Max.traveling speed (Loaded/Unloaded)	km/h	17/19		17/19		19/20		19/19		17/19		17/19		19/20		19/20	
Lifting Speed (Loaded/Unloaded)	mm/s	560/600		560/600		500/550		400/420		520/570		520/570		420/480		370/410	
Lowing Speed (Loaded/Unloaded)	mm/s	450/500		450/500		450/550		350/400		450/500		450/500		450/550		350/400	
Drive and transmission control device																	
Engine mode		ISUZU C240						ISUZU 4JG2				GCT K25					
Engine rated power	kW/rpm	35.4/2500						44.9/2450				37.4/2400					
Engine rated torque	Nm/rpm	139.9/1800						184.7/1600~1800				176.5/1600					
Engine cylinder number-borexstroke		4-86×102						4-95.4x107				4-89×100					
Engine displacement	L	2.369						3.05				2.488					
Engine type		Diesel										Gasoline or LPG					
Emission		Euro Stage IIIA															
Battery(Voltage/Capacity)	V/Ah	12/80										12/60					
Engine fuel tank capacity	L							60									
Transmission box shifting gears (Front/Rear type)								1-1Power Shift T/M / 2-2 Manual Shift T/M									
Note: *stands for theoretical calculating value.																	

Note:*stands for theoretical calculating value.

Engine Model and Main Specification for Option						
Engine model	Rated power/ rotating speed (Kw/rpm)	Rated power/ rotating speed (Nm/rpm)	Engine displacement (L)	Engine cylinder number	Cylinder number - BorexStroke	Engine type
ISUZU 4JG2	35/2450	170/1700	3.05	4	4-95.4x107	Diesel
KUBOTA V2403	34.1/2400	155.9/1600	2.434	4	4-87×102.4	Diesel
Cummins QSF2.8	36/2500	186/1100~1500	2.8	4	4-94x100	Diesel
Cummins QSF2.8	43/2500	186/1100~1500	2.8	4	4-94x100	Diesel
DACHAI CA498	45/2500	196/1800	3.168	4	4-98x105	Diesel
JMC HJ493	39/2500	165/1800	2.771	4	4-93x102	Diesel
JMC HJ493G43	36.5/2500	156/1800	2.771	4	4-93x102	Diesel
GCT K21	31.2/2200	143.7/1600	2.065	4	4-89x83	Gasoline or LPG
Mitsubishi 4G64	GAS:48/2700 LPG:46/2700	GAS:170/2400 LPG:168/1600	2.351	4	4-86.5×100	Gasoline or LPG
Mitsubishi S4S	35.3/2250	177/1700	3.331	4	4-94×120	Diesel

WIDE VIEW FULL FREE 2-STAGE MAST																	
Mast model	Max. lifting height mm	Load capacity (load center 500mm)					Mast overall height (fork to the ground)			Free lifting height (with backrest)			Service weight				Mast tilting angle (°) α/β
		CPQ(Y)D20/ CPC20/CPCD20	CPQ(Y)D25/ CPC25/CPCD25	CPQ(Y)D30/ CPC30/CPCD30	CPQ(Y)D35/ CPC35/CPCD35		2-2.5t	3t	3.5t	2-2.5t	3t	3.5t	CPQ(Y)D20/ CPC20/CPCD20	CPQ(Y)D25/ CPC25/CPCD25	CPQ(Y)D30/ CPC30/CPCD30	CPQ(Y)D35/ CPC35/CPCD35	
ZM200	2000	2000	2500	3000	3500	1495	1570	1680	495	340	460	3470	3850	4330	4770	6/12	
ZM250	2500	2000	2500	3000	3500	1745	1820	1930	745	590	710	3515	3895	4370	4820	6/12	
ZM300	3000	2000	2500	3000	3500	1995	2080	2180	995	840	960	3550	3945	4420	4870	6/12	
ZM330	3300	2000	2500	3000	3500	2145	2220	2330	1145	990	1110	3595	3975	4445	4895	6/12	
ZM350	3500	2000	2500	3000	3500	2245	2320	2430	1245	1090	1210	3615	3995	4465	4915	6/12	
ZM370	3700	2000	2500	3000	3500	2345	2420	2530	1345	1200	1310	3635	4015	4480	4935	6/6	
ZM400	4000	2000	2500	3000	3500	2545	2620	2730	1545	1390	1510	3705	4085	4550	5000	6/6	
ZM425	4250	2000	2500	3000	3500	2670	2745	2855	1670	1515	1635	3730	4110	4575	5025	6/6	
ZM450	4500	2000	2500	3000	3500	2795	2870	2980	1795	1640	1760	3755	4135	4595	5050	6/12	
ZM500	5000	2000	2500	3000	3500	3045	3120	3230	2045	1890	2010	3805	4185	4640	5110	6/6	
ZM550	5500	2000	2500	3000	3500	3345	3420	3530	2345	2190	2310	3890	4270	4830	5295	3/6	
ZM600	6000	2000	2500	3000	3500	3595	3670	3780	2595	2440	2560	3935	4315	4875	5350	3/6	